



# Technical Specification

Page 1 of 1

GrayLastic form liners provide maximum design latitude for precast or cast-in-place applications. They are re-usable up to 100 times, and are especially economical for applications that require an extended, reusable formliner.

Many patterns are available in sizes up to 30' long, and all GrayLastic form liners can be easily field-cut. Odd sizes or custom fabrications are available for special applications.

GrayLastic elastomeric formliners are manufactured from 100% polyurethane and are usually mold bonded to plywood. They are easily attached to most concrete forming systems, including wood, steel, aluminum and fiberglass.

<b>TECHNICAL DATA:</b>		<b>ASTM</b>
Shore A Hardness	60-70	D2240
Cast Density, PCF	62-67	
Tear Strength, PLI	140-160	D624
Tensile Strength, psi	1300-1600	D638 (D412)
Ultimate Elongation	280-330%	D638 (D412)

## Manufacturing Tolerances

Mold bonded to 0.75" plywood:  $\pm 0.125$ " (length and width)

Unbonded (custom order only):  $\pm 1$ " (length and width)



1500 E. Chestnut Avenue  
Santa Ana, CA 92701  
Phone: 714.547.6710  
Outside CA: 800.547.7760  
Fax: 714.245.9715  
[www.formliners.com](http://www.formliners.com)